

DATASHEET

FUJITSU ESPRIMO E5730

DESKTOP PC

YOUR DESKTOP PC WITHOUT ANY COMPROMISES

ESPRIMO E5730

As a Small Form Factor PC the ESPRIMO E5730 is the ideal choice for your desk. Depending on the space you have available, you can position the PC vertically or horizontally - without any additional feet. Equipped with Intel® chipset and processor technology the high performance levels of this efficient and quiet PC meet the requirements of your daily business applications.



SMALL FORM FACTOR PC

Flexible desktop solution whatever the space required.

- Less than 13 litres volume; also usable as a thin client

ENVIRONMENTALLY COMPATIBLE PRODUCT

Your contribution to environmental protection for the continued existence of our planet

- Halogen-free mainboard, sophisticated product concept for the entire lifecycle

QUIET

Pleasant working environment due to an extremely quiet system



- Innovative hardware design, optimized cooling concept



SERVICEABILITY

Simple extendability and optimal user-friendliness without any additional tools

- Easy access to all replaceable and expandable components



COMPONENTS

PROCESSOR

Intel® Core™2 Quad processor Q9650 (4C/4T, 3.0 GHz, 12 MB, 1333 MHz)
Intel® Core™2 Quad processor Q9550 (4C/4T, 2.83 GHz, 12 MB, 1333 MHz)
Intel® Core™2 Quad processor Q9505 (4C/4T, 2.83 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Quad processor Q9400 (4C/4T, 2.66 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Quad processor Q8300 (4C/4T, 2.5 GHz, 4 MB, 1333 MHz)
Intel® Core™2 Duo processor E8600 (2C/2T, 3.33 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E8500 (2C/2T, 3.16 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E8400 (2C/2T, 3.0 GHz, 6 MB, 1333 MHz)
Intel® Core™2 Duo processor E7600 (2C/2T, 3.06 GHz, 3 MB, 1066 MHz)
Intel® Core™2 Duo processor E7500 (2C/2T, 2.93 GHz, 3 MB, 1066 MHz)
Intel® Pentium® processor E6300 (2C/2T, 2.8 GHz, 2 MB, 1066 MHz)
Intel® Pentium® processor E5400 (2C/2T, 2.7 GHz, 2 MB, 800 MHz)
Intel® Pentium® processor E5200 (2C/2T, 2.5 GHz, 2 MB, 800 MHz)
Intel® Celeron® processor E3200 (2C/2T, 2.4 GHz, 1 MB, 800 MHz)
Intel® Celeron® processor 450 (1C/1T, 2.2 GHz, 512 KB, 800 MHz)

MEMORY MODULES

1 GB (1 module(s) 1 GB) DDR2, 800 MHz, PC2-6400, DIMM
2 GB (1 module(s) 2 GB) DDR2, 800 MHz, PC2-6400, DIMM
4 GB (1 module(s) 4 GB) DDR2, 800 MHz, PC2-6400, DIMM

HARD DISK DRIVES (INTERNAL)

SSD SATA, 128 GB, 2.5-inch
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
CF module IDE, 512 MB
CF module IDE, 4 GB, (300x)
CF module IDE, 1 GB

Hard disk notes

Supporting NCQ and 3 GBit
CF Modules for thin client usage (with or without embedded software)

GRAPHICS ADD ON CARDS (OPTIONAL)

Dual DVI Adapter
DVI Adapter
NVIDIA® Geforce® 9300GE low profile, 256 MB
NVIDIA® Geforce® 9300GE low profile, 512 MB
NVIDIA® Geforce® 9500GS low profile, 512 MB
NVIDIA® Quadro NVS 290 low profile, 256 MB

MODULAR BAY OPTIONS

1.44 MB Floppy
Blu-ray Disc Triple Writer, SATA I
DVD-ROM, SATA I
DVD Super Multi, SATA I
MultiCard Reader 20in1, 3,5-Inch, USB 2.0

INTERFACE ADD ON CARDS/COMPONENTS (OPTIONAL)

WLAN III, 802.11g/Draft-n (Windows only)
WLAN II, 802.11g, 54Mbps (Windows only)
Parallel Interface
Modem adapter kit (EU)
Modem 56k incl. RJ11 modem cable
Gigabit Ethernet PCIe x1
FireWire PCI-Card IEEE1394
eSATA Interface
Dual serial card PCI LP

Base unit ESPRIMO E5730

MAINBOARD

Mainboard type D2824
Formfactor proprietary
Chipset Intel® Q43
Processor socket LGA 775
Processor quantity maximum 1
System bus (FSB / HT / QPI) up to 1333 MHz
Memory slots 4 DIMM (DDR2)
Supported capacity RAM (max.) 16 GB
Memory frequency 800 MHz
Memory notes With future modules.
Dual channel support.
For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN 10/100/1000 MBit/s Intel® 82567 LF
BIOS version Phoenix 6.0
BIOS features BIOS Flash EPROM update by software
Recovery BIOS
Audio codec Realtek ALC663
Audio features Internal speaker supports audio playback, High Definition audio

I/O CONTROLLER ON BOARD

Serial ATA total 4
thereof eSATA 2 (optional)
Controller functions Serial ATA II
NCQ and 3 GBit
AHCI

INTERFACES

Audio: line-in 1
Audio: line-out 1
USB 2.0 total 12
USB front 2
USB rear 6
USB internal 4
VGA 1
DVI optional
Serial (RS-232) 2 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2) 2
Ethernet (RJ-45) 1
Parallel optional (25pin with EPP and ECP)

INPUT DEVICE / COMPONENTS

Optical USB tilt wheel mouse
Optional: Optical USB/PS2 tilt wheel mouse

DRIVE BAYS

Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"

SLOTS

PCI-Express 2.0 x16	1 x (210 mm) low profile
PCI-Express x4 (mech. x8)	1 x (210 mm) low profile
PCI (32-bit / 33 MHz)	2 x (190 mm) low profile
Slots optional configuration	or 1x PCI Express x16 low profile (190mm) and via Riser 2 x PCI full height (174 / 210 mm)

GRAPHICS ON BOARD

Graphics brand name	Intel® GMA 4500
Shared video memory	up to 256 MB
Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
TFT resolution (VGA)	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
Graphics features	DirectX 10
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

ELECTRICAL VALUES

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 71% / 77% / 76%
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Operating voltage range	90 - 264 V
Operating line frequency range	47 - 63 Hz
Max. output of power supply	270 W
Power factor correction/active power	active
Monitor outlet	Switched

POWER CONSUMPTION

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=b1474376-699a-48e4-ad14-a3ab9d93ceb0

HEAT DISSIPATION

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)

Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™2 Duo E8600
Noise Operation mode 1: ODD load (Blue angel requirement)	5.0 B / 36 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.5 B / 19 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	3.7 B / 22 dB(A)

NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)

Noise Operation mode 4: High load	3.7 B / 22 dB(A)
Noise Operation mode 5: Office applications	3.5 B / 19 dB(A)
Idle mode (Blue Angel requirement)	3.5 B / 19 dB(A)
Noise notes / description	A weighted sound power level L _{wad} (in B) / workplace related A-weighted sound pressure level L _{pAm} (in dB(A)), Bystander position

DIMENSIONS / WEIGHT / ENVIRONMENTAL

Dimensions (W x D x H)	340 x 380 x 100 mm
Operating position	Vertical / horizontal (no feet needed)
Weight	approx. 10 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	15 - 35°C

COMPLIANCE

Product	ESPRIMO E5730
Model	DT7-2824
Germany	GS optional
Europe	CE Nordic Swan in progress
USA/Canada	FCC Class B UL cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

OPERATING SYSTEM

Operating system optional preinstalled	Microsoft® Windows® 7 Home Premium Microsoft® Windows® 7 Professional Microsoft® Windows Vista® Home Basic Microsoft® Windows Vista® Home Premium Microsoft® Windows Vista® Business 32-bit Microsoft® Windows Vista® Business 64-bit TwinLoad Microsoft® Windows® XP Professional (DVD)
Operating system compatible	Linux
Operating system notes	All Windows Vista® and Windows® 7 versions are Office 2007 ready.

ADDITIONAL SOFTWARE

Additional software (preinstalled)	Nero Essentials S (burning software)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive)

COMPATIBILITY (REFERENCES)

	DMI 2.0 PC 2001 WMI 1.5 USB 2.0
--	--

MANAGEABILITY

Manageability features	ASF 2.0 (Alert Standard Format) DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional) PXE 2.1 Boot code BootP Boot Code including Bootmanage Administrator Software (tested) Wake up from S5 (off mode) Intrusion switch (optional) Intel® Standard Manageability
Manageability type	DeskView 10.x client management including:

MANAGEABILITY

DeskView features	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Advanced alerts (ASF implementation) Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu

SECURITY

Physical security	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock
System security	Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Boot protection for floppy disk / CD drive and write protection for floppy disk drive Control of external interfaces
User security	User and supervisor BIOS password SystemLock 2 BIOS SmartCard Security Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader

SERVICEABILITY

FlexySlot
EasyFix
EasyChange for HDD
EasyChange for optical drives

PACKAGING INFORMATION

Packaging dimension	500x290x540 mm
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (g) EPS / PS	230 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process

WARRANTY

MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION

Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu ESPRIMO E5730, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu ESPRIMO E5730, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://ts.fujitsu.com/ESPRIMO>

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions
Website: <http://ts.fujitsu.com>
2010-02-01 CE-EN
